

SOHO CABINET

Technical Details



Material	0,8 mm steel
Color	RAL 7035 or RAL 9005
Maximum Static Load	Up to 80 kg.
Finish	Electrostatic Powder Paint

Standard Configuration:

- Steel Frame
- Glass door with cylindrical lock
- 1 pair of 19" mounting rails
- Low cost alternative
- RoHS compliant, UL certified
- Solid, lightweight and ergonomic
- The glass door is concealed inside the cabinet and to minimize the risk of impact from the edges.
- Easy to assemble and flatpack option available

Order Information

Height (U)	Outer Width (W) mm	Outer Depth (D) mm	Outer Height (H) mm	Inner Width mm	Inner Depth mm	Inner Height mm	19" Rails Adjustable Depth Range (c)	X	Y	Weight (kg)	Part No	Back Cover Part No
4U	545	400	222	488	370	190	55-325	457	147	6	WC1S-X-04J4A	WSZ-X-04JY0-0901
4U	545	600	222	488	570	190	55-535	457	147	7	WC1S-X-04J6A	WSZ-X-04JY0-0901
4U	600	400	222	541	370	190	55-325	510	147	7	WC1S-X-0464A	WSZ-X-046Y0-0901
4U	600	600	222	541	570	190	55-535	510	147	9	WC1S-X-0466A	WSZ-X-046Y0-0901
6U	545	400	311	488	370	280	55-325	457	236	8	WC1S-X-06J4A	WSZ-X-06JY0-0901
6U	545	600	311	488	570	280	55-535	457	236	9	WC1S-X-06J6A	WSZ-X-06JY0-0901
6U	600	400	311	541	370	280	55-325	510	236	8	WC1S-X-0664A	WSZ-X-066Y0-0901
6U	600	600	311	541	570	280	55-535	510	236	10	WC1S-X-0666A	WSZ-X-066Y0-0901
7U	545	400	355	488	370	324	55-325	457	280	9	WC1S-X-07J4A	WSZ-X-07JY0-0901
7U	545	600	355	488	570	324	55-535	457	280	10	WC1S-X-07J6A	WSZ-X-07JY0-0901
7U	600	400	355	541	370	324	55-325	510	280	9	WC1S-X-0764A	WSZ-X-076Y0-0901
7U	600	600	355	541	570	324	55-535	510	280	11	WC1S-X-0766A	WSZ-X-076Y0-0901
9U	545	400	444	488	370	414	55-325	457	369	10	WC1S-X-09J4A	WSZ-X-09JY0-0901
9U	545	600	444	488	570	414	55-535	457	369	11	WC1S-X-09J6A	WSZ-X-09JY0-0901
9U	600	400	444	541	370	414	55-325	510	369	12	WC1S-X-0964A	WSZ-X-096Y0-0901
9U	600	600	444	541	570	414	55-535	510	369	13	WC1S-X-0966A	WSZ-X-096Y0-0901
12U	545	400	577	488	370	547	55-325	457	503	11	WC1S-X-12J4A	WSZ-X-12JY0-0901
12U	545	600	577	488	570	547	55-535	457	503	12	WC1S-X-12J6A	WSZ-X-12JY0-0901
12U	600	400	577	541	370	547	55-325	510	503	13	WC1S-X-1264A	WSZ-X-126Y0-0901
12U	600	600	577	541	570	547	55-535	510	503	15	WC1S-X-1266A	WSZ-X-126Y0-0901
15U	545	400	711	488	370	680	55-325	457	636	13	WC1S-X-15J4A	WSZ-X-15JY0-0901
15U	545	600	711	488	570	680	55-535	457	636	15	WC1S-X-15J6A	WSZ-X-15JY0-0901
15U	600	400	711	541	370	680	55-325	510	636	16	WC1S-X-1564A	WSZ-X-156Y0-0901
15U	600	600	711	541	570	680	55-535	510	636	17	WC1S-X-1566A	WSZ-X-156Y0-0901

(Color Code): 7:RAL 7035 Light Grey, 9:RAL 9005 Black